



New Pacific Metals Corp.

TSX-V: NUAG | OTCQX: NUPMF

NEWS RELEASE

Trading Symbol: TSX-V: NUAG / OTCQX: NUPMF

NEW PACIFIC REPORTS FIRST RESULTS FROM 2018 DRILL PROGRAM AT SILVER SAND, BOLIVIA –

**Near Surface Silver Mineralization Intercepted in 94 out of 98 holes;
Numerous Significant Intercepts include 76.63 metres grading 383 g/t**

VANCOUVER, British Columbia – January 22, 2019 -- New Pacific Metals Corp. (TSX-V: NUAG) (OTCQX: NUPMF) (“New Pacific” or the “Company”) is pleased to announce the first batch of drill results from its wholly-owned Silver Sand Project in Potosí Department, Bolivia.

The drilling program commenced in mid-October 2017. A total of 55,010 metres in 195 HQ size diamond core drill holes had been completed by mid-December 2018. The drill program covers an area of approximately 1,600 m long in the north-south direction and up to 800 m wide in the east-west direction. The holes were drilled along northeast 60 degree oriented sections with a 50 m spacing between the sections. Most drill holes are drilled at dip angle of 45 degrees to penetrate the principal trend of the mineralized structure zones with an average hole length of approximately 285 m. To date, assay results of drill core samples of 98 holes have been received and analyzed, of which 94 holes intercepted silver mineralization.

Highlights of significant drill intersections are summarized as follows (for a detailed list, please refer to *Table-1 – Composited Drill Intersections of Mineralization* below):

- Drill hole DSS525001, **135.72m @ 240 g/t Ag** from 50.8m to 186.52m,
*incl. 76.63m @ 383g/t Ag from 50.8m to 127.43m, and
incl. 7.64m @ 406g/t Ag from 178.88m to 186.52m;*
- Drill hole DSS525002, **273.94m @ 84g/t Ag** from 0.92m to 274.86m,
*incl. 13.44m @ 205g/t Ag from 86.3m to 99.74m, and
incl. 56.3m @ 216g/t Ag from 148.5m to 204.8m;*
- Drill hole DSS5803, **172m @ 110g/t Ag** from 18.0m to 190.0m,
incl. 83.5m @ 192g/t Ag from 18.0m to 101.5m;
- Drill hole DSS525009, **178.99m @ 96g/t Ag** from 59.9m to 238.89m,
incl. 18.03m @ 362g/t Ag from 126.49m to 144.52m;
- Drill hole DSS525010, **106.4m @ 154g/t Ag** from 12.0m to 118.4m,
*incl. 38.75m @ 165g/t Ag from 12.0m to 50.75m, and
incl. 4.03m @ 2,366g/t Ag from 92.43m to 96.46m;*
- Drill hole DSS5407, **76.03m @ 205g/t Ag** from 64.07m to 140.10m,
incl. 60.89m @ 251g/t Ag from 64.07m to 124.96m;

- Drill hole DSS665001, **89.77m @ 115g/t Ag** from 44.23m to 134.1m,
*incl. 4.45m @ 394g/t Ag from 44.23m to 48.68m,
incl. 37.15m @ 149g/t Ag from 58.0m to 95.15m, and
3.52m @ 430g/t Ag from 213.82m to 217.34m;*
- Drill hole DSS6603A, **65.25m @ 181g/t Ag** from 7.9m to 73.15m,
incl. 32.0m @ 304g/t Ag from 7.9m to 39.9m;
- Drill hole DSS6402, **157.68m @ 66g/t Ag** from 18.1m to 175.78m,
incl. 26.16m @ 252g/t Ag from 74.22m to 100.38m;
- Drill hole DSS645001, **85.54m @ 119g/t Ag** from 27.46m to 113.0m,
*incl. 26.04m @ 189g/t Ag from 27.46m to 53.5m, and
incl. 31.16m @ 156g/t Ag from 81.84m to 113.0m;*
- Drill hole DSS5806, **146.69m @ 63g/t Ag** from 13.96m to 160.65m,
incl. 9.34m @ 208g/t Ag from 13.96m to 23.3m;
- Drill hole DSS5404, **106.5m @ 86g/t Ag** from 87.0m to 193.5m,
incl. 28.5m @ 220g/t Ag from 87.0m to 115.5m;
- Drill hole DSS525003, **102m @ 82g/t Ag** from 47.3m to 149.3m,
incl. 13.36m @ 475g/t Ag from 100.5m to 113.86m;
- Drill hole DSS645002, **173.34m @ 48g/t Ag** from 23.21m to 196.55m,
incl. 54.49m @ 111g/t Ag from 23.21m to 77.7m;
- Drill hole DSS6608, **188.79m @ 43g/t Ag** from 58.7m to 247.49m;
- Drill hole DSS6201, **69.67m @ 116g/t Ag** from 119.93m to 189.6m;
- Drill hole DSS6403, **191.35m @ 42g/t Ag** from 82.15m to 273.5m;
- Drill hole DSS525005, **102.65m @ 66g/t Ag** from 28.35m to 131.0m,
incl. 5.2m @ 342g/t Ag from 93.92m to 99.12m;
- Drill hole DSS4603, **159.71m @ 41 g/t Ag** from 41.59m to 201.3m,
*incl. 6.23m @ 223g/t Ag from 97.77m to 104.0m, and
incl. 2.0m @ 522g/t Ag from 174.62m to 176.62m;*
- Drill hole DSS4804, **23.1m @ 138g/t Ag** from 123.9m to 147.0m,
*incl. 1.06m @ 1,070g/t Ag from 145.94m to 147.0m, and
20.0m @ 164g/t Ag, 3.62% Pb from 249.5m to 269.5m;*
- Drill hole DSS525004, **79.16m @ 78g/t Ag** from 45.92m to 125.08m,
incl. 22.32m @ 118g/t Ag from 73.54m to 95.86m;
- Drill hole DSS5601, **62.87m @ 96g/t Ag** from 85.43m to 153.0m,
- Drill hole DSS545001, **62.6m @ 95g/t Ag** from 63.83m to 126.43m,
incl. 14.71m @ 212g/t Ag from 97.16m to 111.87m;
- Drill hole DSS4802, **21.09m @ 269g/t Ag** from 92.45m to 113.54m,
incl. 2.33m @ 1,099g/t Ag from 92.45m to 94.78m;
- Drill hole DSS6607, **122.72m @ 46g/t Ag** from 28.4m to 151.12m, and
incl. 1.0m @ 2,530g/t Ag, 1.19% Pb, 1.05% Zn from 204.52m to 205.52m;
- Drill hole DSS4604, **5.06m @ 1,104g/t Ag** from 107.07m to 112.13m;
- Drill hole DSS5003, **65.99m @ 83g/t Ag** from 62.46m to 128.45m,

- incl. 19.81m @ 175g/t Ag from 108.64m to 128.45m;*
- Drill hole DSS6202, **64.26m @ 84g/t Ag** from 306.14m to 370.4m,
incl. 17.43m @ 183g/t Ag from 323.57m to 341.0m;
- Drill hole DSS665003, **81.68m @ 65g/t Ag** from 71.6m to 153.28m,
incl. 6.84m @ 229g/t Ag from 93.76m to 100.6m;
- Drill hole DSS6401, **84.79m @ 58g/t Ag** from 12.32m to 97.11m,
- Drill hole DSS5202, **59.6m @ 82g/t Ag** from 4.2m to 63.8m,
incl. 4.3m @ 311g/t Ag from 4.2m to 8.5m;
- Drill hole DSS525008, **63.1 m @ 75g/t Ag** from 1.7m to 64.8m,
incl. 6.7m @ 213g/t Ag from 49.7m to 56.4m;
- Drill hole DSS7001, **60.32m @ 76g/t Ag** from 70.03m to 130.35m,
incl. 32.77m @ 113g/t Ag from 90.36m to 123.13m;
- Drill hole DSS6603, **15.93m @ 265g/t Ag** from 7.17m to 23.1m (hole failed in mineralization);
- Drill hole DSS6802, **69.06m @ 50g/t Ag** from 86.17m to 156.3m,
incl. 7.64m @ 164g/t Ag from 86.17m to 93.81m;
- Drill hole DSS525013, **25.13m @ 136g/t Ag** from 39.57m to 64.7m;
- Drill hole DSS525011, **54.3m @ 60g/t Ag** from 144.0m to 198.3m,
incl. 3.5m @ 433g/t Ag from 169.6m to 173.1m;
- Drill hole DSS6604, **56.79m @ 56g/t Ag** from 0.0m to 56.79m,
*incl. 25.22m @ 113g/t Ag from 31.57m to 56.79m; and
incl. 3.0m @ 779g/t Ag from 50.0m to 53.0m;*
- Drill hole DSS6801, **75.4m @ 42g/t Ag** from 55.5m to 130.9m,
incl. 10.0m @ 130g/t Ag from 55.5m to 65.5m.

(True width of the mineralization is unknown, but based on the current understanding of the relationship between drill direction and the mineralized structures it is estimated that true width will approximate 80% of the down hole interval length. Please refer to Table-1 – Composited Drill Intersections of Mineralization below for details.)

Based on the drilling results, the drill holes usually penetrate first through an up to 50 m thick layer of reddish siltstone and mudstone units of Cretaceous Tarapaya Formation, then into massive altered white colour arenites or sandstones units of the Cretaceous La Puerta Formation, where silver mineralization occurs. At the contact of these two units, massive pyrite mineralization of less than two metres in thickness, typically occurs. Tin mineralization in the district is often associated with massive pyrite. At depth, many drill holes end at the reddish sandstones units of the Cretaceous La Puerta Formation. This Cretaceous Formations sit unconformably on a basement of tightly folded and faulted Paleozoic marine clastic sediments.

The mineralized sandstone and siltstone units of the Cretaceous Formations are shallow dipping or sub-horizontal, and gently folded into open synclines and anticlines with their hinges shallowly plunging to North-North-West (“NNW”) direction. To the north of Silver Sand, the Cretaceous sediments were

intruded and cut by numerous porphyritic dacitic sills and dykes of Miocene age, which are believed to be closely associated with silver mineralization in the district.

Silver mineralization is observed to be associated with fractures and alterations in the sandstones units, which were bleached white due to sericite alteration of original reddish sandstones, resulting in a sub-horizontal mineralizing zone of up to more than two hundred metres in thickness beneath the Tarapaya red siltstone and mudstone. The mineralized fractures generally extend NNW, sub-vertically and slightly dipping west. The mineralized bodies were detected by drilling within an area of up to 1,600 m long in north-south direction and 800 m wide in east-west direction within the Silver Sand property limit and remain open to both the north and the west. Mineralizing bodies were oxidized to various extents to depth.

Silver mineralization is characterized by sheeted veins, stockwork veinlets, crackle veins and breccia zones of sulfosalts and sulfides containing silver in altered sandstones. The most common silver-containing sulfosalt is freibergite, associated with a small amount of miargyrite, polybasite, bournonite, boulangerite, andorite and bismuthinite.

Using the section 60 as a dividing line, to its south, Tarapaya red siltstones and mudstones were mostly eroded away and massive whitish altered and fractured sandstones of the La Puerta Formation exposed at surface. Extensive mining remains of adits, drifts and stopes of colonial times exist at the steep slopes and cliffs that have more than 150 m relief with the workings extending into the mountain. Drilling in this area has hit many of these ancient underground workings. Silver mineralization to the south of section 60 was outlined by drilling an area of approximately 500 m long and 150 m wide the altered quartz sandstones of the La Puerta Formation, extending from surface to a depth of more than 300 m.

To the north of section 60, drilling covered an area of approximately 1,100 m long north-south and 800 m wide in the east-west direction. Drilling in this area intercepted mineralized fracture zones right beneath the Tarapaya reddish siltstones and mudstones. The mineralization could extend from near surface to a depth up to more than 250 m. In comparison to the south of section 60, only a few ancient underground mining workings were encountered during drilling. Mineralization remains open along strike and at depth in both the southern area and the northern area.

Quality Assurance and Quality Control

HQ size drill core samples from altered and mineralized intervals were split into halves by diamond saw cutting with an average sample interval of one to one and half metres long at the Company's core processing facility located in Betanzos, a local town 20 kilometres away from the project site. Half core samples are stored in secured core storages for future reference, and the other half core samples were shipped in security sealed bags to ALS Global in Oruro, Bolivia for preparation, and ALS Global in Lima, Peru for geochemical analysis with the code of OG46 for elements of silver, lead and zinc. Silver overlimits further go to gravimetric analysis with the code of GRA21.

A standard quality assurance and quality control ("QAQC") protocol was employed to monitor the quality of sample preparation and analysis. Standards of certified reference materials, blanks and

duplicates were inserted in normal core sample sequences prior to shipment to lab at a ratio of 20:1, i.e., every twenty samples contain at least one standard sample, one blank sample and one duplicate sample. The assay results of QAQC samples did not show any significant bias of analysis or contamination during sample preparation.

Technical information contained in this news release with respect to New Pacific has been reviewed and approved by Alex Zhang, P. Geo., Vice President of Exploration, who is a Qualified Person for the purposes of National Instrument 43-101 – Standards of Disclosure for Mineral Projects (“NI 43-101”).

ABOUT NEW PACIFIC

New Pacific is a Canadian exploration and development company which owns the Silver Sand Project in Potosí Department of Bolivia, the Tagish Lake gold project in Yukon, Canada and the RZY Project in Qinghai Province, China. Its largest shareholders are Silvercorp Metals Inc. (TSX/NYSE American: SVM) and Pan American Silver Corp. (TSX/NASDAQ: PAAS), one of the world's largest primary silver producers, which operates six mines, including the San Vicente mine located in the Potosí Department of Bolivia.

For further information, contact:

New Pacific Metals Corp.
Gordon Neal
President
Phone: (604) 633-1368
Fax: (604) 669-9387
info@newpacificmetals.com
www.newpacificmetals.com

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this news release.

CAUTIONARY NOTE REGARDING FORWARD-LOOKING INFORMATION

Certain of the statements and information in this press release constitute “forward-looking information” within the meaning of applicable Canadian provincial securities laws. Any statements or information that express or involve discussions with respect to predictions, expectations, beliefs, plans, projections, objectives, assumptions or future events or performance (often, but not always, using words or phrases such as “expects”, “is expected”, “anticipates”, “believes”, “plans”, “projects”, “estimates”, “assumes”, “intends”, “strategies”, “targets”, “goals”, “forecasts”, “objectives”, “budgets”, “schedules”, “potential” or variations thereof or stating that certain actions, events or results “may”, “could”, “would”, “might” or “will” be taken, occur or be achieved, or the negative of any of these terms and similar expressions) are not statements of historical fact and may be forward-looking statements or information.

Forward-looking statements or information are subject to a variety of known and unknown risks, uncertainties and other factors that could cause actual events or results to differ from those reflected in the forward-looking statements or information, including, without limitation, risks relating to: fluctuating equity prices, bond prices,

commodity prices; calculation of resources, reserves and mineralization, foreign exchange risks, interest rate risk, foreign investment risk; loss of key personnel; conflicts of interest; dependence on management and others.

This list is not exhaustive of the factors that may affect any of the Company's forward-looking statements or information. Forward-looking statements or information are statements about the future and are inherently uncertain, and actual achievements of the Company or other future events or conditions may differ materially from those reflected in the forward-looking statements or information due to a variety of risks, uncertainties and other factors, including, without limitation, those referred to in the Company's Annual Information Form for the year ended June 30, 2018 under the heading "Risk Factors". Although the Company has attempted to identify important factors that could cause actual results to differ materially, there may be other factors that cause results not to be as anticipated, estimated, described or intended. Accordingly, readers should not place undue reliance on forward-looking statements or information.

The Company's forward-looking statements or information are based on the assumptions, beliefs, expectations and opinions of management as of the date of this press release, and other than as required by applicable securities laws, the Company does not assume any obligation to update forward-looking statements or information if circumstances or management's assumptions, beliefs, expectations or opinions should change, or changes in any other events affecting such statements or information. For the reasons set forth above, investors should not place undue reliance on forward-looking statements or information.

CAUTIONARY NOTE TO US INVESTORS

This news release has been prepared in accordance with the requirements of NI 43-101 and the Canadian Institute of Mining, Metallurgy and Petroleum Definition Standards, which differ from the requirements of U.S. Securities laws. NI 43-101 is a rule developed by the Canadian Securities Administrators that establishes standards for all public disclosure an issuer makes of scientific and technical information concerning mineral projects.

Table-1 – Compositd Drill Intersections of Mineralization

Hole_id	Section		Mineralized Intervals						Notes
			From (m)	To (m)	Length (m)	Ag_g/t	Pb_%	Zn_%	
DSS245001	2450		no significant results						
DSS3201	32		31.18	32.68	1.50	34	0.02	0.03	
			126.81	128.30	1.49	88	0.08		
			167.30	176.07	8.77	101	0.01		
DSS3401	34		183.20	184.30	1.10	31	0.46	0.01	
			210.05	211.08	1.03	59	0.12		
			215.20	216.26	1.06	37	0.18		
DSS3402	34		226.72	227.73	1.01	34	0.03	0.23	
DSS3403	34		157.90	177.10	19.20	39	0.20		
			193.55	194.68	1.13	30	0.11		
			221.18	222.20	1.02	57	0.50		
DSS3601	36		no significant results						
DSS3801	38		372.22	373.34	1.12	34	0.51	0.06	
DSS3802	38		163.50	169.36	5.86	44	0.04		
			254.41	255.49	1.08	57	0.15		
			266.15	267.36	1.21	149	0.03		
DSS385001	3850		100.00	105.35	5.35	76	0.32	0.01	
			187.70	188.80	1.10	40	0.78		
			199.50	201.50	2.00	42	0.12		
			225.75	232.35	6.60	63	0.03		
DSS4001	40		no significant results						
DSS4002	40		136.60	138.75	2.15	81	0.26		
			251.70	255.60	3.90	170	0.20		
			276.27	281.30	5.03	170	0.11		
			303.50	304.53	1.03	36	0.10		
DSS405001	4050		79.36	90.80	11.44	43	0.11		
			173.09	179.42	6.33	142	0.30		
			184.00	185.13	1.13	86	0.31		
DSS4201	42		134.22	154.76	20.54	33	0.17	0.02	
DSS4202	42		75.10	78.17	3.07	41	0.19		
			84.85	86.02	1.17	32	0.23		
			98.30	105.15	6.85	62	0.08		
			118.30	119.30	1.00	111	0.09		
			125.60	127.75	2.15	84	0.02		
			179.04	205.92	26.88	102	0.10		
		<i>incl.</i>	<i>179.04</i>	<i>195.30</i>	<i>16.26</i>	<i>158</i>	<i>0.13</i>		
DSS4203	42		148.50	161.10	12.60	37	0.60	0.06	
DSS4401	44		209.12	210.20	1.08	42	0.10	0.01	
			218.52	222.67	4.15	84	2.38		
			275.80	277.00	1.20	42	0.40		
DSS4403	44		130.63	138.12	7.49	76	2.00	0.03	
			217.13	221.72	4.59	60	1.45		
DSS4404	44		87.45	97.98	10.53	77	0.03	0.05	
			138.33	139.45	1.12	59	0.13		
DSS4405	44	<i>incl.</i>	73.40	100.50	27.10	106	0.05		
			<i>97.40</i>	<i>100.50</i>	<i>3.10</i>	<i>725</i>	<i>0.17</i>		

DSS445002	4450		85.06	88.62	3.56	114	0.13	0.02	
			156.09	192.23	36.14	38	1.04	0.07	
			263.22	264.33	1.11	50	0.41	0.02	
			303.23	312.89	9.66	40	0.04	0.02	
DSS4602	46		173.35	189.72	16.37	48	1.10	0.03	
DSS4603	46	<i>incl.</i>	41.59	201.30	159.71	41	0.01	0.07	
			<i>incl.</i>	97.77	104.00	6.23	223	0.04	
			<i>incl.</i>	174.62	176.62	2.00	522	0.07	
DSS4604	46		107.07	112.13	5.06	1104	0.46	0.04	
			173.39	174.48	1.09	63	0.05	0.03	
DSS4605	46		101.25	126.50	25.25	49	0.04		
DSS4606	46		81.15	82.20	1.05	44	1.36	0.06	
			101.97	115.10	13.13	43	0.64	0.02	
			128.78	132.00	3.22	41	0.84	0.01	
			156.02	157.07	1.05	36	0.92	0.03	
			216.30	223.30	1.00	55	0.55	0.05	
DSS465002	4650		84.05	86.30	2.25	36		0.01	
			107.00	112.05	5.05	33		0.01	
			121.00	142.85	21.85	21	0.01	0.07	
			150.50	151.50	1.00	332	0.11	0.06	
			215.33	216.50	1.17	43	0.07	0.01	
			227.10	228.35	1.25	102	0.16	0.18	
			252.10	253.30	1.20	38	0.07	0.07	
			259.00	260.10	1.10	31	0.06	0.01	
			268.10	270.10	2.00	64	1.54	0.01	
DSS465003	4650		119.07	126.80	7.73	30	0.69	0.02	
			153.12	154.20	1.08	53	1.91	0.02	
			191.80	199.30	7.50	63	1.39	0.04	
DSS465004	4650	<i>incl.</i>	47.10	120.30	73.20	35	0.13	0.45	
			<i>incl.</i>	117.04	120.30	3.26	155	0.35	0.50
			127.50	128.60	1.10	59	0.02	0.03	
			138.40	139.40	1.00	87	0.01	0.02	
			158.20	159.53	1.33	73	0.02		
			195.50	199.85	4.35	380	0.07	0.73	
DSS4801	48		59.30	143.78	84.48	31	0.15	0.04	
DSS4802	48	<i>incl.</i>	29.21	33.08	3.87	353	0.07	0.06	
			<i>incl.</i>	31.80	33.08	1.28	1045	0.01	0.09
			<i>incl.</i>	92.45	113.54	21.09	269	0.11	0.01
DSS4803	48		92.45	94.78	2.33	1099	0.42	0.01	
			85.45	86.53	1.08	314	0.38	0.01	
DSS4804	48		91.26	92.30	1.04	87	0.03		
			<i>incl.</i>	67.10	72.56	5.46	70	0.02	
78.45	81.00	2.55		52	0.14				
123.90	147.00	23.10		138	0.02				
145.94	147.00	1.06		1070	0.13	0.01			
162.25	163.25	1.00		74	0.03	0.02			
174.60	176.90	2.30		141	0.05	0.01			
DSS4805	48		249.50	269.50	20.00	164	3.62	0.01	
			82.35	87.25	4.90	58	0.02		
			122.15	123.20	1.05	55	0.90	0.01	
			134.00	137.00	3.00	100	2.74	0.01	

			165.43	166.87	1.44	73	1.77	0.04
			175.55	179.00	3.45	40	1.13	0.10
			210.90	212.00	1.10	274	2.23	0.12
			221.37	222.61	1.24	105	0.20	0.02
			241.00	242.22	1.22	69	0.45	
DSS485001	4850		90.05	98.86	8.81	79	0.02	0.01
			104.38	115.89	11.51	82	0.05	0.04
			126.81	129.98	3.17	58	0.28	0.01
			151.09	155.62	4.53	90	2.98	0.03
			235.18	236.28	1.10	102	0.10	
			242.47	244.81	2.34	59	0.17	
			247.11	249.42	2.31	50	0.14	0.02
			259.46	260.77	1.31	62	0.08	
DSS485002	4850		33.66	34.76	1.10	59	0.18	0.03
			55.30	56.30	1.00	55	0.32	0.04
			85.45	86.65	1.20	37	0.09	0.01
			89.00	90.20	1.20	143	0.02	
			96.05	97.21	1.16	381	0.14	
			102.04	103.25	1.21	60	0.06	
			150.30	151.40	1.10	111	0.07	
			162.23	163.27	1.04	109	0.03	0.01
DSS485003	4850		56.97	58.12	1.15	41	0.05	
			82.65	84.92	2.27	67	0.02	
			95.75	96.94	1.19	43	0.02	
			112.43	113.76	1.33	75	0.02	0.01
			248.17	249.45	1.28	55	0.23	
			254.67	264.20	9.53	77	1.48	0.01
			282.53	293.60	11.07	130	0.27	
DSS5003	50		62.46	128.45	65.99	83	0.07	0.06
		<i>incl.</i>	108.64	128.45	19.81	175	0.08	0.01
DSS505002	5050		18.42	19.67	1.25	77		
			58.10	60.60	2.50	44		
			65.40	67.86	2.46	182	0.01	
			79.40	80.60	1.20	55	0.01	
			103.50	109.58	6.08	76	0.03	
			153.30	156.60	3.30	107	0.05	0.01
			168.75	169.90	1.15	195	0.07	0.01
			176.00	187.86	11.86	37	0.34	
			203.75	214.33	10.58	93	0.09	
			283.04	286.49	3.45	244	0.09	
			290.16	291.46	1.30	53	0.02	0.02
			309.60	310.80	1.20	228	0.02	0.01
			316.00	317.20	1.20	203	0.03	
DSS5202	52		4.20	63.80	59.60	82	0.01	
		<i>incl.</i>	4.20	8.50	4.30	311		
			178.10	180.20	2.10	45	0.12	
			210.50	212.60	2.10	89	0.02	0.17
			246.31	247.45	1.14	102	0.15	
DSS5205	52		61.00	67.50	6.50	54	0.08	
			97.25	98.30	1.05	264	0.32	0.12
			106.36	107.60	1.24	125	0.01	0.01
			112.15	113.30	1.15	241	0.06	

			129.50	131.55	2.05	104	0.02		
			137.00	142.45	5.45	43	0.03	0.03	
			150.60	151.60	1.00	49	0.05		
			177.58	180.10	2.52	31	0.03	0.06	
DSS525001	5250	<i>incl.</i>	50.80	186.52	135.72	240			
		<i>incl.</i>	50.80	127.43	76.63	383	0.08	0.01	
			178.88	186.52	7.64	406	0.06	0.01	
			254.30	255.80	1.50	157	0.06	0.00	
DSS525002	5250	<i>incl.</i>	0.92	274.86	273.94	84	0.10	0.01	8.10m minedout
		<i>incl.</i>	86.30	99.74	13.44	205	0.04	0.07	
		<i>incl.</i>	148.50	204.80	56.30	216	0.32		8.10m minedout
DSS525003	5250	<i>incl.</i>	47.30	149.30	102.00	82	0.06	0.05	
			100.50	113.86	13.36	475	0.19	0.01	
DSS525004	5250	<i>incl.</i>	25.38	26.55	1.17	127	0.07	0.01	
			45.92	125.08	79.16	78	0.03	0.02	
			73.54	95.86	22.32	118	0.03		
			171.86	178.24	6.38	46	0.01		
			228.33	234.46	6.13	153	0.13	0.01	
DSS525005	5250	<i>incl.</i>	28.35	131.00	102.65	66	0.02	0.04	
			93.92	99.12	5.20	342	0.04		
			148.67	149.85	1.18	90	0.01		
DSS525006	5250		14.40	55.00	40.60	58	0.05	0.52	
			76.10	78.81	2.71	116	0.01	0.01	
			85.65	89.70	4.05	192	0.04	0.01	
DSS525007	5250		140.79	141.95	1.16	44	0.02	0.02	
			163.85	165.00	1.15	68	0.38	1.00	
DSS525008	5250	<i>incl.</i>	1.70	64.80	63.10	75	0.06		
			49.70	56.40	6.70	213	0.15		
			132.52	134.77	2.25	45	0.05	0.05	
			187.22	188.24	1.02	144	0.02	0.06	
			194.40	195.63	1.23	41	0.03		
			211.64	216.24	4.60	84	0.34	0.07	
			218.40	219.53	1.13	46	0.01		
			231.58	232.86	1.28	42	0.02	0.01	
DSS525009	5250	<i>incl.</i>	59.90	238.89	178.99	96	0.03	0.02	
			126.49	144.52	18.03	362	0.03		
DSS525010	5250	<i>incl.</i>	12.00	118.40	106.40	154	0.04	0.03	
		<i>incl.</i>	12.00	50.75	38.75	165	0.04	0.04	
		<i>incl.</i>	92.43	96.46	4.03	2366	0.42		
			144.10	146.20	2.10	41	0.08		
			211.33	213.60	2.27	80	0.06		
DSS525011	5250	<i>incl.</i>	144.00	198.30	54.30	60	0.02	0.09	
			169.60	173.10	3.50	433	0.02	0.03	
DSS525012	5250		11.00	39.30	28.30	38	0.01		
			83.30	84.40	1.10	376	0.02	0.01	
			232.60	252.85	20.25	181	0.02	0.04	
DSS525013	5250		39.57	64.70	25.13	136	0.02	0.03	
DSS5403	54		13.15	14.65	1.50	192	0.10		
			34.55	38.60	4.05	239	0.05		
			147.90	152.50	4.60	55	0.03		
DSS5404	54		35.50	37.00	1.50	131	0.02	0.01	

			44.00	45.00	1.00	109	0.33	0.00	
			87.00	193.50	106.50	86	0.07	0.05	
		<i>incl.</i>	87.00	115.50	28.50	220	0.11	0.13	
DSS5405	54		hole failed and terminated prior to planned depth						
DSS5406	54		32.90	34.90	2.00	237	0.05		
			145.67	195.00	49.33	43	0.04	0.10	
		<i>incl.</i>	194.00	195.00	1.00	1100	0.40	0.10	
DSS5407	54		64.07	140.10	76.03	205	0.09	0.01	
			64.07	124.96	60.89	251	0.10	0.01	
		<i>incl.</i>	247.40	248.90	1.50	150	0.03	0.01	
DSS545001	5450		50.32	59.26	8.94	9	0.21	2.31	
			63.83	126.43	62.60	95	0.04	0.01	
		<i>incl.</i>	97.16	111.87	14.71	212	0.08	0.01	
DSS5601	56		34.22	41.30	7.08	191	0.11	0.02	
			85.43	153.00	62.87	96	0.03		
			184.16	190.16	6.00	147	0.05	0.01	
DSS5602	56		16.55	17.90	1.35	70	0.01	0.02	
			27.55	30.15	2.60	54	0.03	0.02	
			119.10	120.32	1.22	92	0.10	0.43	
			124.35	132.50	8.15	65	0.05	0.03	
			148.28	152.40	4.12	236	0.05	0.39	
DSS5603	56		6.06	7.09	1.03	81			
			24.00	29.30	5.30	59	0.01		
			47.50	50.60	3.10	83	0.04		
			77.00	78.00	1.00	95	0.02		
			82.33	83.00	0.67	58	0.10		
			87.36	98.50	11.14	172	0.09		
DSS5605	56		17.00	35.90	18.90	31	0.01	0.01	
DSS565001	5650		6.30	7.52	1.22	83	0.01	0.01	
			55.58	80.00	24.42	106	0.03		
			103.07	104.30	1.23	56	0.05		
			139.82	141.00	1.18	265	0.28	1.51	
			156.39	157.45	1.06	79	0.02	0.01	
			161.00	162.12	1.12	49	0.02		
			192.84	193.90	1.06	49	0.02		
DSS5801	58		2.00	26.00	24.00	67	0.03		
		<i>incl.</i>	20.00	26.00	6.00	211	0.08	0.11	
			114.36	115.74	1.38	520	0.01	2.18	
			137.77	141.13	3.36	84	0.03	0.01	
			162.76	164.70	1.94	711	0.19	1.90	
			192.06	201.25	9.19	105	0.24	1.56	
DSS5802	58		212.00	227.60	15.60	77	0.14	0.64	
		<i>incl.</i>	212.00	213.00	1.00	991	0.31	0.86	
			249.65	264.14	14.49	62	0.05	0.07	
DSS5803	58		18.00	190.00	172.00	110	0.03	0.03	
		<i>incl.</i>	18.00	101.50	83.50	192	0.04		
DSS5804	58		18.19	102.40	84.21	33	0.04	0.02	
DSS5805	58		17.10	18.39	1.29	344	0.14		
			49.48	61.71	12.23	69	0.13		
DSS5806			13.96	160.65	146.69	63	0.06	0.02	
		<i>incl.</i>	13.96	23.30	9.34	208	0.03	0.25	

5.36m minedout

21.55m minedout

			260.15	261.24	1.09	53	0.05		
			264.74	265.90	1.16	48	0.05		
			267.00	268.11	1.11	55	0.02		
DSS6001	60		100.67	140.60	39.93	49	0.07	0.32	
DSS6002	60		48.28	57.17	8.89	93	0.18	0.11	
			103.92	110.24	6.32	38	0.11		
			152.00	177.93	25.93	54	0.09	0.19	
			203.59	213.84	10.25	45			
			239.30	242.40	3.10	154			
DSS6003	60		116.45	117.45	1.00	43			
			155.77	157.27	1.50	32	0.01		
DSS6004	60		29.00	30.00	1.00	122			
DSS6201	62		20.85	22.00	1.15	55	0.02	0.01	
			29.52	31.02	1.50	245	7.13	0.01	
			99.75	100.85	1.10	106	0.19	0.33	
			105.74	109.50	3.76	70	0.12	0.01	
			119.93	189.60	69.67	116	0.07	0.02	
			205.10	206.40	1.30	48	0.04	0.21	
			252.50	253.60	1.15	66	0.08	1.19	2.7m minedout
DSS6202	62		21.68	22.70	1.02	45	0.01		
			27.27	28.30	1.03	68	0.02	0.12	
			233.00	235.00	2.00	57	0.01	0.01	
			262.56	283.42	20.86	84	0.12	0.30	
			306.14	370.40	64.26	84	0.13	0.07	
		<i>incl.</i>	323.57	341.00	17.43	183	0.09	0.01	
			379.73	380.73	1.00	35	0.53	1.05	
			383.11	384.15	1.04	197	1.10	0.55	
			388.40	391.55	3.15	222	0.33	0.51	
			404.05	406.63	2.58	96	0.07	0.10	
DSS6203	62		25.37	26.35	0.98	52	0.33	1.90	
			30.89	31.89	1.00	39	0.24	0.03	
			295.00	296.00	1.00	362	0.13	1.10	
DSS6401	64		12.32	97.11	84.79	58	0.05	0.02	20m minedout
DSS6402	64		18.10	175.78	157.68	66	0.07	0.19	15.79m minedout
		<i>incl.</i>	74.42	100.38	26.16	252	0.09		9.12m minedout
DSS6403	64		40.75	42.20	1.45	117	0.15		
			82.15	273.50	191.35	42			
DSS645001	6450		27.46	113.00	85.54	119	0.06	0.01	7.85m minedout
		<i>incl.</i>	27.46	53.50	26.04	189	0.05		
		<i>incl.</i>	81.84	113.00	31.16	156	0.09	0.02	4.48m minedout
			231.50	235.98	4.48	250	0.39	1.15	
DSS645002	6450		23.21	196.55	173.34	48	0.05	0.19	
		<i>incl.</i>	23.21	77.70	54.49	111	0.04	0.01	
			202.42	203.86	1.44	45	0.03	0.01	
			205.30	206.70	1.40	42	0.03	0.09	
			212.58	213.80	1.22	47	0.18	0.08	
DSS645003	6450		35.40	36.44	1.04	74	0.06	0.13	
DSS6603	66		7.17	23.10	15.93	265	0.05		
			24.43	26.00	1.57	15	0.18	3.39	terminated in mineralization
DSS6603A	66		7.90	73.15	65.25	181	0.08	0.10	
		<i>Incl.</i>	7.90	39.90	32.00	304	0.08	0.15	

			179.32	180.60	1.28	114	0.47	0.87	
			204.86	207.42	2.56	215	0.02	0.08	
DSS6604	66	<i>incl.</i>	0.00	56.79	56.79	56	0.04	0.04	
			50.00	53.00	3.00	779	0.07	0.01	
			70.50	71.93	1.43	84	0.02	0.01	
			89.50	91.00	1.50	77	0.34	0.01	
			220.10	223.15	3.05	79	0.01		
			231.45	232.50	1.05	39	0.33	0.01	
			245.85	247.00	1.15	56	0.36		
			255.65	256.80	1.15	43	0.04		
			275.28	276.30	1.02	38	0.02		
DSS6605	66		30.71	36.14	5.43	32	0.04		
			53.85	58.00	4.15	110	0.03		
			228.24	266.00	37.76	30	0.13		
		<i>incl.</i>	253.70	256.40	2.70	128	0.03		terminated in mineralization
DSS6606	66		58.57	59.60	1.03	391	0.03		
			64.40	65.60	1.20	126	0.05		
			132.50	133.77	1.27	72	0.01		
			230.12	231.50	1.80	39	0.06	0.01	
DSS6607	66		28.40	151.12	122.72	46	0.07	0.10	31m minedout
			204.52	205.52	1.00	2530	1.19	1.05	
			222.74	223.81	1.07	410	0.18	2.23	
			228.30	229.38	1.08	60	0.59		
DSS6608	66		58.70	247.49	188.79	43	0.08	0.10	
			269.24	272.19	2.95	69	0.15	0.04	
			281.55	282.92	1.37	74	0.04	0.02	
			296.75	300.90	4.15	69	0.05	0.04	
DSS665001	6650	<i>incl.</i>	44.23	134.00	89.77	115	0.12	0.31	7.3m minedout
		<i>incl.</i>	44.23	48.68	4.45	394	0.06	0.01	
			58.00	95.15	37.15	149	0.17	0.34	7.3m minedout
			170.60	172.80	2.20	51	0.14	0.06	
			177.60	178.82	1.22	60	0.11	0.21	
			213.82	217.34	3.52	430	0.41	0.13	
DSS665002	6650	<i>incl.</i>	61.60	188.23	126.63	44	0.16	0.43	
			162.00	164.10	2.10	708	1.45	2.19	
			231.04	232.04	1.00	80	0.18	2.37	
DSS665003	6650		60.00	61.00	1.00	57	0.01		
			71.60	153.28	81.68	65	0.05	0.10	
		<i>incl.</i>	93.76	100.60	6.84	229	0.03	0.01	
			261.30	269.40	8.10	67	0.01		
DSS6801	68	<i>incl.</i>	31.65	32.65	1.00	73	0.01		
			55.50	130.90	75.40	42	0.09	0.09	
			55.50	65.50	10.00	130	0.06		
			232.25	234.25	2.00	121	0.11	0.01	
			257.40	259.40	2.00	189	0.24	1.08	
			307.10	314.75	7.65	99	0.03	0.07	
DSS6802	68	<i>incl.</i>	20.90	32.15	11.25	79			
			86.17	156.30	69.06	50	0.10	0.06	
			86.17	93.81	7.64	164	0.04		
			188.45	190.45	2.00	35	0.25	0.02	

			208.50	244.30	35.80	33	0.06	0.05
			271.70	274.00	2.30	38	0.05	
DSS685001	6850		76.00	109.30	33.30	82	0.16	0.03
			121.87	126.00	4.13	58	0.13	0.28
			148.10	150.15	2.05	57	0.54	2.73
			176.00	177.00	1.00	79	0.68	0.33
			197.20	199.70	2.50	47	0.02	
			208.25	212.70	4.45	127	0.10	0.19
DSS7001	70		20.60	21.82	1.22	30	0.37	0.19
			31.00	38.95	7.95	64	0.22	0.00
			70.03	130.35	60.32	76	0.11	0.13
		<i>incl.</i>	90.36	123.13	32.77	113	0.16	0.23
			148.90	154.75	5.85	122	0.02	0.02
			165.01	166.27	1.26	41	0.02	0.00
DSS7201	72		232.14	233.40	1.26	85	0.05	0.06
			301.73	303.16	1.43	95		

Notes:

1. "g/t" = grams per metric tonne.
2. Table-1 shows composited intervals from the drilling program that average greater than 30 g/t. These composited intervals may include samples containing less than 30 g/t between higher grade samples.
3. "Length (m)" is the drill core length in metres. The true width of the mineralized zones is estimated to be approximately 80% of the drill intervals based on the current understanding of the relationship between drill direction and the angles of the mineralized structures.